

## Application Tape

<b>Product Category</b>	Application tape
<b>Description</b>	<p>Transparent polyethylene film, 150 my.          Used to transfer decals and die cut lettering from the silicone paper liner to the final surface of application (panels, windows, walls, foam board, etc.). The special flat spreading of the acrylic modified adhesive guarantees an easy transfer of letters and very easy removal of the application tape. The film transparency allows perfect positioning.  <b>SHELF LIFE:</b> 1 year when stored in the original packaging between 20°C and 25°C at 50% relative humidity .</p>
<b>Standard heights</b>	610 mm – code: 000959 / 1220 mm – code: 000960
<b>Standard length</b>	100 m

CHARACTERISTICS:	Unit	Value	Tolerance	Norm
Low density/ high density PE	mm	0,150	± 10%	ASTM D374
Adhesive :		modified acrylic		
Total thickness	mm	0,160	± 10%	ASTM D374
Adhesion on steel	N/”	2,5	± 0,5	AFERA 4001
Tear resistance	N/”	1	± 0,5	AFERA 4001
Adhesion on vinyl	N/”	3	± 0,5	AFERA 4001
Rolling ball tack	Cm	20	Maximum	PSTC 6
Dimensional stability		Good		
Application temperature	°C	-10 / +40		
Service temperature	°C	-20 / +80		
Labels removal		Good		