

CAD-CAM FILMS

Fluo | Varnish | Fatty



Fluo



BF FLU020A
NEON YELLOW



BF FLU030A
NEON ORANGE



BF FLU040A
NEON PINK



BF FLU050A
NEON GREEN



BF FLU046A
NEON BLUE

Varnish



BF V700A
VARNISH WHITE




BF V710A
VARNISH BLACK



BF V730A
VARNISH RED

Fatty



BF T700
WHITE FATTY



BF T720
MEDIUM YELLOW FATTY



BF T734
ORANGE FATTY



BF T730
RED FATTY



BF T740
ROYAL BLUE FATTY



BF T710
BLACK FATTY



FLUO



VARNISH

BF FLUO

B-FLEX SERIES FLUO is a polyurethane fluo opaque film, suitable for heat transfer on cotton fabrics, polyester and acrylic garments. Its polyester adhesive carrier allows for easy repositioning of characters accidentally removed.

B-FLEX SERIES FLUO can be pressed on T-shirts, sportswear or uniforms for work. Because the material is thin and elastic, the fabric underneath remains soft and pliable.

SUGGESTED FABRICS:
cotton, polyester, mixed, printed with NON sublimatic colors.

CUT:
cutting plotter, 45° blade, laser.

WASHING:
wait 12 hours after application.

Minimum cutting size **0,8** cm

COMPOSITION
PU Polyurethane

TECHNICAL FEATURES

THICKNESS
90 μ



MATTE FINISHING



OPAQUE



ADHESIVE LINER



MIRROR CUT



APPLICATION

TEMPERATURE
145°C - 295°F



10"



3,5 bar



LINER REMOVAL
HOT



WASHING

60°



DRYER



FIND MORE HERE



BF VARNISH

B-FLEX SERIES VARNISH is a polyurethane super glossy film, suitable for heat transfer on cotton fabrics, polyester and acrylic garments. Its polyester adhesive carrier allows for easy repositioning of characters accidentally removed.

B-FLEX SERIES VARNISH can be pressed on T-shirts, sportswear or uniforms for work. Because the material is thin and elastic, the fabric underneath remains soft and pliable.

SUGGESTED FABRICS:
cotton, polyester, mixed, printed with NON sublimatic colors.

CUT:
cutting plotter, 45° blade, laser.

WASHING:
wait 12 hours after application.

Minimum cutting size **1,0** cm

COMPOSITION
PU Polyurethane

TECHNICAL FEATURES

THICKNESS
100 μ



GLOSSY FINISHING



OPAQUE



ADHESIVE LINER



MIRROR CUT



APPLICATION

TEMPERATURE
145°C - 295°F



10"



3,5 bar



LINER REMOVAL
HOT



WASHING

40°



FIND MORE HERE



BF FATTY

B-FLEX SERIES FATTY is a polyurethane opaque and thick film, suitable for heat transfer on cotton fabrics, polyester and acrylic garments. Its polyester adhesive carrier allows for easy repositioning of characters accidentally removed.

B-FLEX SERIES FATTY can be pressed on T-shirts and sportswear or uniforms for work and is ideal for smaller logos and designs to add extra dimension to your garments.

SUGGESTED FABRICS:
cotton, polyester, mixed, printed with NON sublimatic colors.

CUT:
cutting plotter, 60° blade.

WASHING:
wait 12 hours after application.

Minimum cutting size **2,0** cm

COMPOSITION
PU Polyurethane

TECHNICAL FEATURES

THICKNESS
550 μ



MATTE FINISHING



OPAQUE



ADHESIVE LINER



MIRROR CUT



APPLICATION

TEMPERATURE
140°C - 285°F



30"



2,0 bar



LINER REMOVAL
HOT



WASHING

40°



FIND MORE HERE

