

CAD-CAM FILMS

BF 700A



BF 700A
WHITE



BF 736A
PINK



BF 744A
LIGHT BLUE



BF 783A
AQUAMARINE



BF 728A
LEMON YELLOW



BF 738A
CYCLAMEN



BF 741A
POWDER BLUE



BF 782A
TURQUOISE



BF 720A
MEDIUM YELLOW



BF 739A
VELVET RED



BF 746A
SKY BLUE



BF 710A
BLACK



BF 722A
PUMPKIN YELLOW



BF 761A
AUBERGINE



BF 751A
LIME GREEN



BF 714A
GREY



BF 734A
ORANGE



BF 770A
PURPLE



BF 752A
APPLE GREEN



BF 712A
LIGHT GREY



BF 732A
FLAME RED



BF 748A
NAVY BLUE



BF 754A
GRASS GREEN



BF 766A
BEIGE



BF 730A
RED



BF 742A
ELECTRIC BLUE



BF 750A
GREEN



BF 763A
CAPPUCCINO



BF 762A
BORDEAUX



BF 740A
ROYAL BLUE



BF 780A
FOREST GREEN



BF 764A
LEATHER



BF 737A
BLUSH PINK



BF 743A
LILAC



BF 781A
OLIVE GREEN



BF 760A
BROWN

BF 700 A

B-FLEX SERIES 700A is a polyurethane opaque film suitable for heat transfer on cotton fabrics, cotton and polyester and polyester and acrylic garments. Its polyester adhesive carrier allows for easy repositioning of characters accidentally removed.

B-FLEX SERIES 700A can be pressed on T-shirts, sportswear or uniforms for work. Because the material is thin and elastic, the fabric underneath remains soft and pliable. It is also great for multilayer applications.

SUGGESTED FABRICS:
cotton, polyester, mixed, printed with NON sublimatic colors.

CUT:
cutting plotter, 45° blade, laser.

WASHING:
wait 12 hours after application.

STANDARDS:
Oeko-Tex Standard 100 Class I.



0,5 cm Minimum cutting size

PU COMPOSITION
PU Polyurethane

TECHNICAL FEATURES

THICKNESS 90 μ	MATTE FINISHING	OPAQUE	ADHESIVE LINER	MIRROR CUT

APPLICATION

TEMPERATURE 140°C - 285°F	10"	3,5 bar	LINER REMOVAL HOT

WASHING

90°	DRY CLEANING	DRYER



FIND MORE HERE

